

MLFB-Ordering data

6SL3210-5BB11-2BV1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																						
Input <table> <tr> <td>Number of phases</td><td>1 AC</td></tr> <tr> <td>Line voltage</td><td>200 ... 240 V -15 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	1 AC	Line voltage	200 ... 240 V -15 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor λ</td><td>0.72</td></tr> <tr> <td>Offset factor $\cos \varphi$</td><td>0.95</td></tr> <tr> <td>Efficiency η</td><td>0.98</td></tr> <tr> <td>Filter class (integrated)</td><td>Class B</td></tr> </table>	Power factor λ	0.72	Offset factor $\cos \varphi$	0.95	Efficiency η	0.98	Filter class (integrated)	Class B								
Number of phases	1 AC																						
Line voltage	200 ... 240 V -15 % +10 %																						
Line frequency	47 ... 63 Hz																						
Power factor λ	0.72																						
Offset factor $\cos \varphi$	0.95																						
Efficiency η	0.98																						
Filter class (integrated)	Class B																						
Output <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>230 V</td></tr> <tr> <td>Rated power (HO)</td><td>0.12 kW / 0.16 hp</td></tr> <tr> <td>Rated power (LO)</td><td>0.12 kW / 0.12 hp</td></tr> <tr> <td>Rated current (HO)</td><td>0.90 A</td></tr> <tr> <td>Rated current (LO)</td><td>0.90 A</td></tr> </table>	Number of phases	3 AC	Rated voltage	230 V	Rated power (HO)	0.12 kW / 0.16 hp	Rated power (LO)	0.12 kW / 0.12 hp	Rated current (HO)	0.90 A	Rated current (LO)	0.90 A	Ambient conditions <table> <tr> <td>Cooling</td><td>convection cooling</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> Ambient temperature <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> Relative humidity <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	convection cooling	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																						
Rated voltage	230 V																						
Rated power (HO)	0.12 kW / 0.16 hp																						
Rated power (LO)	0.12 kW / 0.12 hp																						
Rated current (HO)	0.90 A																						
Rated current (LO)	0.90 A																						
Cooling	convection cooling																						
Installation altitude	1000 m (3281 ft)																						
Operation	-10 ... 60 °C (14 ... 140 °F)																						
Storage	-40 ... 70 °C (-40 ... 158 °F)																						
Max. operation	95 %																						
<table> <tr> <td>Pulse frequency</td><td>8.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Pulse frequency	8.00 kHz	Output frequency	0 ... 550 Hz	Communication <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																
Pulse frequency	8.00 kHz																						
Output frequency	0 ... 550 Hz																						
Communication	USS, Modbus RTU																						
	Standards <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																		
Compliance with standards	CE, cULus, C-Tick (RCM), KC																						
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																						

Overload capability

Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s

SIEMENS

Data sheet for SINAMICS V20

MLFB-Ordering data 6SL3210-5BB11-2BV1



Figure similar

Mechanical data	Connections
-----------------	-------------

Mounting position	Wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSAA
Net weight	0.60 kg (1.32 lb)
Width	68.0 mm (2.68 in)
Height	142.0 mm (5.59 in)
Depth	107.8 mm (4.24 in)

Max. motor cable length	
Shielded	25 m (82 ft)
Unshielded	50 m (164 ft)

Inputs / outputs

Standard digital inputs	
Number	4

Digital outputs	
Number as relay changeover contact	1
Number as transistor	1

Analog inputs	
Number	2 (Can be used as additional digital input)

Analog outputs	
Number	1