

### MLFB-Ordering data

6SL3210-5BE31-8UV0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data	General tech. specifications																														
<b>Input</b> <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Line voltage</td><td>380 ... 480 V -15 % +10 %</td></tr> <tr> <td>Line frequency</td><td>47 ... 63 Hz</td></tr> </table>	Number of phases	3 AC	Line voltage	380 ... 480 V -15 % +10 %	Line frequency	47 ... 63 Hz	<table> <tr> <td>Power factor <math>\lambda</math></td><td>0.72</td></tr> <tr> <td>Offset factor <math>\cos \varphi</math></td><td>0.95</td></tr> <tr> <td>Efficiency <math>\eta</math></td><td>0.98</td></tr> <tr> <td>Filter class (integrated)</td><td>Unfiltered</td></tr> </table>	Power factor $\lambda$	0.72	Offset factor $\cos \varphi$	0.95	Efficiency $\eta$	0.98	Filter class (integrated)	Unfiltered																
Number of phases	3 AC																														
Line voltage	380 ... 480 V -15 % +10 %																														
Line frequency	47 ... 63 Hz																														
Power factor $\lambda$	0.72																														
Offset factor $\cos \varphi$	0.95																														
Efficiency $\eta$	0.98																														
Filter class (integrated)	Unfiltered																														
<b>Output</b> <table> <tr> <td>Number of phases</td><td>3 AC</td></tr> <tr> <td>Rated voltage</td><td>400 V</td></tr> <tr> <td>Rated power (HO)</td><td>18.50 kW / 25.00 hp</td></tr> <tr> <td>Rated power (LO)</td><td>22.00 kW / 30.00 hp</td></tr> <tr> <td>Rated current (HO)</td><td>38.00 A</td></tr> <tr> <td>Rated current (LO)</td><td>45.00 A</td></tr> <tr> <td>Rated current (HO) at 480V</td><td>34.00 A</td></tr> <tr> <td>Rated current (LO) at 480V</td><td>40.00 A</td></tr> <tr> <td>Pulse frequency</td><td>4.00 kHz</td></tr> <tr> <td>Output frequency</td><td>0 ... 550 Hz</td></tr> </table>	Number of phases	3 AC	Rated voltage	400 V	Rated power (HO)	18.50 kW / 25.00 hp	Rated power (LO)	22.00 kW / 30.00 hp	Rated current (HO)	38.00 A	Rated current (LO)	45.00 A	Rated current (HO) at 480V	34.00 A	Rated current (LO) at 480V	40.00 A	Pulse frequency	4.00 kHz	Output frequency	0 ... 550 Hz	<b>Ambient conditions</b> <table> <tr> <td>Cooling</td><td>External fan</td></tr> <tr> <td>Installation altitude</td><td>1000 m (3281 ft)</td></tr> </table> <b>Ambient temperature</b> <table> <tr> <td>Operation</td><td>-10 ... 60 °C (14 ... 140 °F)</td></tr> <tr> <td>Storage</td><td>-40 ... 70 °C (-40 ... 158 °F)</td></tr> </table> <b>Relative humidity</b> <table> <tr> <td>Max. operation</td><td>95 %</td></tr> </table>	Cooling	External fan	Installation altitude	1000 m (3281 ft)	Operation	-10 ... 60 °C (14 ... 140 °F)	Storage	-40 ... 70 °C (-40 ... 158 °F)	Max. operation	95 %
Number of phases	3 AC																														
Rated voltage	400 V																														
Rated power (HO)	18.50 kW / 25.00 hp																														
Rated power (LO)	22.00 kW / 30.00 hp																														
Rated current (HO)	38.00 A																														
Rated current (LO)	45.00 A																														
Rated current (HO) at 480V	34.00 A																														
Rated current (LO) at 480V	40.00 A																														
Pulse frequency	4.00 kHz																														
Output frequency	0 ... 550 Hz																														
Cooling	External fan																														
Installation altitude	1000 m (3281 ft)																														
Operation	-10 ... 60 °C (14 ... 140 °F)																														
Storage	-40 ... 70 °C (-40 ... 158 °F)																														
Max. operation	95 %																														
	<b>Communication</b> <table> <tr> <td>Communication</td><td>USS, Modbus RTU</td></tr> </table>	Communication	USS, Modbus RTU																												
Communication	USS, Modbus RTU																														
	<b>Standards</b> <table> <tr> <td>Compliance with standards</td><td>CE, cULus, C-Tick (RCM), KC</td></tr> <tr> <td>CE marking</td><td>EN 61800-5-1 /EN 60204-1 and EN 61800-3</td></tr> </table>	Compliance with standards	CE, cULus, C-Tick (RCM), KC	CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																										
Compliance with standards	CE, cULus, C-Tick (RCM), KC																														
CE marking	EN 61800-5-1 /EN 60204-1 and EN 61800-3																														

### Overload capability

#### Low Overload (LO)

110 % rated output current for 60 s, cycle time 300 s

#### High Overload (HO)

150 % rated output current for 60 s, cycle time 300 s



Figure similar

### Mechanical data

Mounting position	Through-hole mounting / wall mounting / side-by-side mounting
Degree of protection	IP20 / UL open type
Size	FSE
Net weight	6.24 kg ( 13.76 lb )
Width	245.0 mm ( 9.65 in )
Height	264.5 mm ( 10.41 in )
Depth	209.0 mm ( 8.23 in )

### Inputs / outputs

#### Standard digital inputs

Number	4
--------	---

#### Digital outputs

Number as relay changeover contact	1
Number as transistor	1

#### Analog inputs

Number	2 (Can be used as additional digital input)
--------	---

#### Analog outputs

Number	1
--------	---

### Connections

#### Max. motor cable length

Shielded	50 m (164 ft)
Unshielded	100 m (328 ft)